

THE REVOLUTION Faster, Better Sinarter

BRK 9120 Series Alarms Introduction and Frequently Asked Questions



Introduction

Introducing the *Revolutionary* 9120 Series smoke alarms and smoke & carbon monoxide combination alarms from BRK. They have been redesigned from the ground up. They install faster, perform better and are even smarter than before. All of these improvements help reduce nuisance alarms and save the Contractor time and money.

For over 40 years, BRK has always maintained our commitment to building the absolute best in home-safety products. The 4120 Series changed the industry in 1998 with contractor preferred features such as a side load battery drawer, battery pull tab and a sleek, low profile design. Now, the new 9120 Series with its new look, "Perfect Mount" gasketless base and Smart Technology all make this alarm the best we have ever developed. We asked you how we could make our alarms better, we listened to what you had to say and we designed our products with you, the professional in mind. The 9120 Series is a Smarter Choice...

Let the Revolution begin.







Question: What's new?

Answer: New Look: The alarm's new look now more closely matches the CO alarms in

the BRK line. This provides a consistent look throughout the home. The Smoke/CO combo alarms are prominently marked with contrasting text to clearly identify CO alarms from smoke alarms in the house.

Smart Technology System designed to help reduce unwanted or nuisance alarms

Single Button Test/Silence eliminates confusion. Depending on what mode the alarm is in, pushing the button provides different functions such as testing the alarm, silencing the alarm, re-testing the alarm when in silence and clearing the Latching feature.

Latching Alarm Indicator easily identifies initiating alarm even after the alarm condition has subsided. Provides easy troubleshooting for improved homeowner satisfaction.

Power-on Silence: the unit will not sound when power is initially supplied

Perfect Mount System includes a gasketless base for easy installation and a new mounting bracket that keeps the alarm secure over a wide rotation range to allow for true alignment.

Improved UV Resistance keeps the alarm from discoloring over time.

Other Contractor Preferred Features include tamper resistant locking pins for the battery drawer and mounting bracket, dust cover, universal mounting bracket with large opening and multiple keyhole slots, side load battery drawer with battery pull tab and AC quick connect power connector.



SMOKE ALARMS





New Part Number: 9120 Series.

Question: What will the 9120 Series replace?

Answer: The 9120 Series will replace all 4120 Series smoke alarms and the SC6120B

smoke/CO combo alarm as per the table below:

Current #	New #	<u>Description</u>
4120	9120	AC BRK Smoke
4120-12ST	9120-12ST	AC BRK Smoke in 12-pack Stadium Tray
4120AB	9120AB	AC/DC BRK Smoke w/Alkaline Battery
4120B	9120B	AC/DC BRK Smoke (includes silence)
86RACHA	9120BA	AC/DC BRK Smoke-Canada
4120B-48B	9120B-48B	AC/DC BRK Smoke 48 bulk pack
4120B-48P	9120B-48P	AC/DC BRK Smoke 48 pack
4120B-GFD	9120B-GFD	AC/DC BRK Smoke Gravity Feed Display
4120LB	9120LB	AC/DC BRK Smoke w/Lithium Battery
4120SAB	Obsolete	Not needed-Silence is a standard feature
4120SB	Obsolete	Not needed-Silence is a standard feature
4120SB-12ST	9120B-12ST	AC/DC BRK Smoke 12 pack Stadium Tray
4120SB2	9120B2	AC/DC BRK Smoke 2 pack
4120SB-48B	Obsolete	Not needed-Silence is a standard feature
41206CP	91206CP	AC BRK Smoke Contractor bulk 6-pack
4120SB6CP	9120B6CP	AC/DC BRK Smoke Contractor bulk 6-pack
4120SB-GFD	Obsolete	Not needed-Silence is a standard feature
4919A	9120A	AC BRK Smoke Canada
8120BL	Obsolete	Not needed. Latching is a standard feature.
SA4120B-48B	SA9120B-48B	AC/DC First Alert Smoke 48 bulk pack
SA4120CN	Obsolete	AC First Alert Smoke-clamshell
SA4121B-48B	Obsolete	Not needed-Silence is a standard feature
SA4121CN	SA9121CN	AC/DC First Alert Smoke-clamshell 3-pack



SMOKE ALARMS





Current #	New #	<u>Description</u>
SC6120B	SC9120B	AC/DC BRK Smoke/CO combo
None	SC9120B-GFD	AC/DC BRK Smoke/CO Gravity Feed Display
None	SC9120BA	AC/DC BRK Smoke/CO combo-Canada
SC6120B-12ST	SC9120B-12ST	AC/DC BRK Smoke/CO combo-12-pack
		stadium tray
SA4121CN3	Obsolete	Replaced by SA9121CN

Question: What's "Smart Technology"?

Answer: "Smart Technology" is a system of improvements designed to work together

to reduce nuisance alarms.

The 9120 Series smoke alarms have a new metal sensing chamber that better insulates the sensor from certain transients (dirty power) transmitted over standard AC house wiring from the power companies.

A redesigned cover top and underneath help to better channel smoke to the sensing chamber and improve horn output.

A new integrated circuit (IC) or brains of the alarm takes multiple looks at conditions that cause the unit to alarm (due to either emergency or non-emergency conditions) versus only once with the 4120 series. This happens before going into alarm, thus reducing the tendency to "nuisance" alarm. Special Note: The SC9120B use a microprocessor vs. an IC as the brains for the alarm and therefore does not utilize "Smart Technology" or have a metal chamber. The SC9120B utilizes Intelligent Sensing Technology™ to achieve similar results.

Question: What happens upon initial power-up or during a loss of power to the 9120

Series Alarm?

Answer: The 9120 series alarm will remain silent upon initial power-up as long as the

battery pull tab is removed prior to AC power being applied. No more alarms or chirps as with the 4120 series. This is especially important after a unit is







in operation and there is a loss of power. Previously, the 4120B might go into alarm upon power-up. The new 9120B will remain silent. Note: If AC power is supplied before battery tab is removed, the unit is performing a normal battery test function and will chirp twice in the first 5 - 10 seconds.

Question: What's different about the "Perfect Mount" mounting system?

Answer: The 9120 Series mounting system has been completely redesigned based on

> our customers' comments. The main difference is that the gasket has been removed. This allows for easier installation. In addition, the alarm will remain secure over a wide rotation range to allow for perfect alignment. The alarm can be rotated past 12:00. When wall mounting, this will allow finetuning on the positioning to compensate for out of aligned wall study and to keep the wording level. The alarm can be positioned over the bracket every 120°. The features that pioneered the industry when the 4120B was introduced have remained. The large holes in the mounting bracket and

keyhole slots have been retained.

Question: Can the 9120 Series alarm fit on the 4120 series mounting bracket?

No. The enhanced alignment features and gasketless base will not allow the Answer:

> 9120 to mount on the old 4120 mounting bracket. However, as with the 4120 series alarms, installation and removal of the mounting bracket is easy with the keyhole slots. The mounting screws do not have to be fully removed. Just back off slightly and twist the bracket to loosen. Then replace with the new 9120 series bracket. The quick-connect power connector is common to all BRK and First Alert hardwired alarms. Therefore, to replace a 4120 series with a 9120 series alarm, all that needs to be done is change the mounting

bracket.







Question: Is the 9120 Series alarm interconnectable with other BRK/First Alert

alarms?

Yes. The 9120 Series is interconnectable with all current BRK and First Alert Answer:

> hardwired smoke, carbon monoxide, heat, hearing impaired alarms and relays. It is interconnectable with up to 18 devices (smoke, carbon

monoxide, heat alarms and relays, etc.), 12 of which can be smoke alarms as

outlined by NFPA.

Question: How do I test the 9120 Series Alarm?

The Single Button Test/Silence feature makes it easy to test the alarm Answer:

individually and when interconnected. Single Station Alarms: Test each smoke alarm. Press and hold the Test/Silence button until the unit alarms. Alarms in an Interconnected Series: Press and hold the Test/Silence button until the unit alarms (about 3 seconds). All interconnected alarms should sound. Important Note: Only the interconnect signal is tested on the other alarms. It does not test each alarm's chamber operation. You must test each alarm individually to check if the alarm is functioning properly. This

is true of all UL listed smoke alarms.

Key Note: Different from the 4120 series, the 9120 series alarms will stop testing immediately upon releasing the test button. This improvement was added to make it easier for inspectors and homeowners to silence the unit quicker. No more going through a complete horn pattern after the button is

released.

Question: What visual indications do I get during testing of an alarm?

Red LED flashes rapidly Answer: On tested alarm

> On all other alarms Green LED(s) on, Red LED is off







Question: How do I silence smoke alarms in an interconnected series:

Answer: Whether with the 9120 Series or other BRK/First Alert smoke alarms, to

silence multiple alarms in an interconnected series, you must press the

Test/Silence button on the unit(s) that triggered the alarm.

Note: The red LED on the initiating alarm will flash rapidly. The red LED will be off on all other non-initiating alarms. New on the 9120 series is that no periodic audible chirp will be heard after the unit is silenced. The unit will exit "silence mode" in approximately 10 minutes. While the unit is in "silence mode" pressing and holding the Test/Silence button for

approximately 10 seconds will test the unit. After testing, the unit will re-

enter "silence mode" and the 10-minute timer will start over.

Question: How does the "Latching Alarm Indicator" work on the 9120 Series alarms?

Answer:

On the 9120 Series Smoke Alarms the "Latching Alarm Indicator" is automatically set when an alarm is initiated. When the alarm condition has subsided the "Latching Alarm Indicator" is set only on the alarm(s) subjected to the nuisance issue. This feature improves homeowner satisfaction by allowing for easy contractor troubleshooting of nuisance alarms with minimal time in the home. No more wasted time and money removing all alarms to resolve a homeowner's concern. The green LED indicator will be on for two seconds/off for two seconds, repeatedly until pushing the Test/Silence button resets the "Latching Alarm Indicator".

After an Alarm (Latching):

On initiating alarm(s) Green LED on for 2 seconds/off for 2 seconds

On all other alarms Green LED on, Red LED is off

The SC9120B is slightly different from the 9120 Series and has not changed from the current SC6120B. The alarms latch in the same manor. That is, when an event triggers an alarm; however the light indicators are different.







After the alarm has "latched", the <u>red</u> LED will flash once every 5 seconds on either the Smoke side, CO side or both, depending on whether smoke, CO or both events have occurred. To clear the "latch" press the Test/Silence" button.

After an Alarm (Latching):

On initiating alarm(s) Red LED(s) flash every 5 seconds On all other alarms Green LED on, Red LED is off

Question: Is the 9120 UL approved?

Answer: Yes. 9120 series smoke alarm meets UL 217 for smoke alarms and

SC9120B meets both UL217 and UL2034 for CO alarms. These alarms also comply with California State Fire Marshall (CSFM), Federal Housing Authority (FHA), Housing and Urban Development

(HUD), National Fire Protection Agency (NFPA) and New York City (MEA).

Question: Does the 9120 have tamper resistant features?

Answer: Yes. The 9120 Series has two locking

features. One to lock the unit to the mounting bracket and one to lock the battery drawer (except 9120 AC only


unit).

Question: Can I use the First Alert Universal

Adapter Plugs with the 9120 Series?

Answer: Yes. Both of the First Alert adapter plugs

(ADK-12) for Kidde and (ADF-12) for Firex alarms have been approved and will work with the 9120 series alarms. The universal adapter plugs allow the connection of









BRK and First Alert hardwired alarms to either Kidde/Fyrnetics or Firex brand hardwired alarms without disconnecting the wires. This is an advantage for retrofitting and maintenance replacement jobs. Saves time and money.

Question: What other "Contractor Preferred" features does the 9120 Series product

line have?

Answer: A Dust Cover is included to keep the alarm clean during construction. Also the same easy Installation/maintenance Features pioneered on the 4120

series have been retained:

Universal bracket works with any standard electrical box up to 4" in size.

- A large opening in the mounting bracket for easy access to wiring.
- A battery pull-tab that keeps battery fresh until the home is occupied.
- A Side Load Battery Drawer allows for easy battery installation/replacement without removing the alarm from the ceiling or wall. (Model 9120B and SC9120B only).
- AC Quick-Connect Power connector
- Keyhole slots in mounting bracket eliminate the need to completely remove the mounting screws from the electrical box to install the bracket.

Question: How long will the battery last under battery backup?

A fresh battery in the 9120B will last up to one year, depending on how old it Answer: was before it was installed and when it was activated. UL 217 mandates that the battery in a backup mode only need to last for 24 hours in standby condition and thereafter be able to be in alarm for at least 4 minutes.

> The SC9120B battery will last for about 20 to 30 days. UL 2034 states that the battery should last for 7 days in standby condition and thereafter be able to be in alarm for at least 4 minutes.







Question: Does the 9120 Series plastic have UV protection?

Answer: Yes. The plastics have been enhanced to include Ultraviolet protection to

help keep the unit from discoloring after prolonged exposure to UV rays. This

can occur if the unit is exposed to the direct rays of the sun, near

fluorescent lighting or other UV sources. Positioning near a skylight or large window can allow the sun to shine directly on the unit for a period of time

during the day.

Question: How does the 9120B stack up against the competition?

Answer: FIREX®

AC Alarms:

406/41216/428 AC/DC Alarms:

4418/4518: This has turned into the price point alarm for Firex. It is an older model lacking many of the expected features by contractors. The 4518 has silence.

- Separate model for Silence
- This still has the battery replacement in the back of the unit. The battery is shipped backwards from the factory so additional labor must be used to reinsert the battery properly.
- The mounting bracket is difficult to use and does not adjust.
- No Latching
- The battery drawer cannot be locked separately from the alarm lock.
- No battery pull tabs

4618: The is Firex's newer model designed to compete with BRK's 4120B. It has added the top load battery drawer.

- No Latching indicator
- Mounting bracket is not adjustable.
- The battery drawer cannot be locked.







- Single button test/silence.
- Battery pull-tab.

5000: The 5000 has Latching added.

- Latching mode is very difficult to distinguish from Silence mode and low battery. Latching: RED light blinks 3 times every minute, Silence: RED light blinks once every 10 seconds and low battery: RED light blinks 4 times every minute.
- Mounting bracket is not adjustable.
- The battery drawer cannot be locked.
- Single button test/silence.
- Battery pull-tab.
- Ramp-up test horn sounds like unit is mal-functioning with its variable sound output.

KIDDE®/FYRNETICS®

AC Alarms: 1235

No model with Silence

AC/DC Alarms: 1275/1275EH: These were Kidde's staple models for AC alarms. They will be replaced by the 1276. These models do have latching but are in a housing that is missing most of the current contractor preferred features:

- Separate model for Silence
- The battery is accessed from the back of the unit
- The mounting bracket is not user friendly

1276: This is the latest introduction from Kidde. They have addressed many of the shortcomings from the old lineup. They almost match up feature for feature with the new 9120B. They do have two separate buttons for test and silence.







<u>USI</u>®

AC Alarms: 1213

AC/DC Alarms: 1204/1209: The 1204/1209 alarms are on an old USI platform that is missing most of the current contractor preferred features:

- Mounting bracket is most difficult to use in the industry. The keyhole slots are covered by foam and are very difficult to locate on the electrical box. Also, it's not adjustable.
- Separate model for Silence
- No Latching
- The battery drawer cannot be locked separately from the alarm lock.
- Single button test/silence on 1204

5204: The USI 5204 is the latest USI model which added a side load battery drawer

- No Latching
- The battery drawer cannot be locked.
- Single button test/silence.

Question: How much more will we charge for all of these features?

Answer: Nothing! All of these features, Latching, Silence, Smart Technology,

Gasketless Base, Perfect Mount System, etc. are at no additional charge from the current pricing of the 4120B. This will allow us to have a tremendous

advantage in the marketplace.

